



INSTALLATION MANUAL

65660AT



230V | COB LED | 10W / 15W / 20W | 50/60Hz | IP20
Aluminium | Adjustable power

Complete with driver.




<p>1</p> <p>To mount the track adaptor into the track system, first check that the selector knob A is at OFF position and the adaptor lock B is disengaged.</p>	<p>2</p> <p>When installing the adaptor into the track, ensure that it is orientated correctly.</p>	<p>3</p> <p>Rotate adaptor lock B clockwise 90° to connect the adaptor to the neutral circuit.</p>															
<p>4</p> <p>Rotate selector knob A to the position of desired circuit.</p>	<p>4a</p> <p>Circuit 1: Rotate the knob A 90° clockwise from the starting position OFF, to connect circuit 1.</p>	<p>4b</p> <p>Circuit 2: Rotate the knob A 90° anti-clockwise from the starting position OFF, to connect circuit 2.</p>															
<p>4c</p> <p>Circuit 3: Rotate the knob A 180° clockwise from the starting position OFF, to connect circuit 3.</p>	<p>5</p> <ol style="list-style-type: none"> 1. Remove screws 2. Remove cover 3. Select the power according to the table <table border="1" data-bbox="563 1653 944 1825"> <tr> <td>10W</td> <td>250mA</td> <td>○</td> <td>●</td> <td>○</td> </tr> <tr> <td>15W</td> <td>350mA</td> <td>○</td> <td>○</td> <td>●</td> </tr> <tr> <td>20W</td> <td>450mA</td> <td>○</td> <td>●</td> <td>●</td> </tr> </table> <p>The default setting is 20W</p> <p>Power selection</p>		10W	250mA	○	●	○	15W	350mA	○	○	●	20W	450mA	○	●	●
10W	250mA	○	●	○													
15W	350mA	○	○	●													
20W	450mA	○	●	●													

Warnings:

1. Make sure that the product is installed properly before connecting to electricity.
2. Do not cover the fitting.
3. Maintenance and installation should only be carried out by a professional electrician.

INSTALLATION MANUAL


65660BT



230V | COB LED | 20W / 25W / 30W / 35W | 50/60Hz
IP20 | Aluminium | Adjustable power

Complete with driver.

90
CRI



1

To mount the track adaptor into the track system, first check that the selector knob **A** is at OFF position and the adaptor lock **B** is disengaged.

2

When installing the adaptor into the track, ensure that it is orientated correctly.

3

Rotate adaptor lock **B** clockwise 90° to connect the adaptor to the neutral circuit.

4

Rotate selector knob **A** to the position of desired circuit.

4a

Circuit 1: Rotate the knob **A** 90° clockwise from the starting position OFF, to connect circuit 1.

4b

Circuit 2: Rotate the knob **A** 90° anti-clockwise from the starting position OFF, to connect circuit 2.

4c

Circuit 3: Rotate the knob **A** 180° clockwise from the starting position OFF, to connect circuit 3.

5

1. Remove screws
2. Remove cover
3. Select the power according to the table

20W	500mA	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>	<input type="radio"/>
25W	600mA	<input type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
30W	750mA	<input checked="" type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input checked="" type="radio"/>
35W	850mA	<input checked="" type="radio"/>	<input type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>

The default setting is 35W

Power selection

Warnings:

1. Make sure that the product is installed properly before connecting to electricity.
2. Do not cover the fitting.
3. Maintenance and installation should only be carried out by a professional electrician.

INSTALLATION MANUAL

65660BTT



LED
BUILT IN



230V | COB LED | 35W | 50/60Hz | IP20 | Dimmable
Aluminium | Adjustable

Complete with dimmable driver.

90
CRI



one
LIGHT

<p>1</p> <p>To mount the track adaptor into the track system, first check that the selector knob A is at OFF position and the adaptor lock B is disengaged.</p>	<p>2</p> <p>When installing the adaptor into the track, ensure that it is orientated correctly.</p>	<p>3</p> <p>Rotate adaptor lock B clockwise 90° to connect the adaptor to the neutral circuit.</p>
<p>4</p> <p>Rotate selector knob A to the position of desired circuit.</p>	<p>4a</p> <p>Circuit 1: Rotate the knob A 90° clockwise from the starting position OFF, to connect circuit 1.</p>	<p>4b</p> <p>Circuit 2: Rotate the knob A 90° anti-clockwise from the starting position OFF, to connect circuit 2.</p>
<p>4c</p> <p>Circuit 3: Rotate the knob A 180° clockwise from the starting position OFF, to connect circuit 3.</p>	<p>5</p>	

Warnings:

1. Make sure that the product is installed properly before connecting to electricity.
2. Do not cover the fitting.
3. Maintenance and installation should only be carried out by a professional electrician.